

# Telex® Technical Data

WLAN / WISP 120 degree Sector Antenna

Order No. 2443AA

2.4 - 2.5 GHz

## General Description

This antenna was designed for WLAN and WISP applications for frequencies of 2400 MHz to 2500 MHz. The antenna has a beamwidth of 120 degrees with a gain of 12 dBi when measured at the standard type-N coax connector. This antenna's mounting bracket features a 0 to 20 degree down tilt adjustment. It is designed to mount to a round mast or a wall.



## Specifications

### Electrical:

Frequency .....	2400-2500 MHz
VSWR.....	nominal 1.6:1, maximum 2.0:1
Nominal Impedance .....	50 ohms
Nominal Gain .....	12 dBi
Half-power H-Plane Beamwidth.....	120 degrees
Half-power E-Plane Beamwidth .....	13 degrees
Front-to-Back Ratio .....	greater than 25 dB
Polarization .....	Vertical
Maximum Power .....	10 Watts

### Mechanical:

Size (without mount).....	5 1/2" wide x 21 1/8" long x 5 1/4" deep
Mounting method.....	adjustable bracket (0 to -20 degrees) with SS U-bolts, 1.0 - 2.0 inch OD
Connector .....	type N female
Wind Survival (per EIA-222-F at 100' height).....	125 mph
Wind Area .....	(0.81 sq. ft. - front, 0.90 sq. ft. - side)
Ice, snow .....	0.5" ice @ 65 mph
Temperature range.....	-40 to +60 degrees C
Humidity .....	5% - 95% (non-condensing)

Since it is the intent of TELEX COMMUNICATIONS, INC. to continually improve its products, Telex reserves the right to make specification and design changes without notice.



8601 East Cornhusker Highway, Lincoln, NE 68505  
Phone: (402) 467-5321 FAX: (402) 467-3279