

Telex® Technical Data

5.8 GHz WLAN/U-NII Directional Antenna
Order No. 5801AN

5.725 - 5.825 GHz

General Description

This antenna was designed for WLAN applications for frequencies of 5725 MHz to 5825 MHz. The antenna is a directional patch that has a gain of 12 dBi when measured at the standard Type N coax connector. This antenna is an excellent choice for a low profile 90 degree sector antenna. It is designed to be mounted to a flat surface or attached to mast brackets. Mast brackets and hardware are supplied.



Specifications

Electrical:

Frequency Range.....	5725-5825 MHz
VSWR.....	nominal 1.4:1 maximum 2.0:1
Nominal Impedance	50 ohms
Gain.....	12 dBi
Front-to-Back Ratio	20 dB
Half-power Azimuth Beamwidth	90 degrees
Half-power Elevation Beamwidth	20 degrees
Polarization.....	Vertical

Mechanical:

Size	5W x 7.75H x 1.125D inches
Mounting Methods, Flat Surface	4 mounting holes, 0.195" dia.
Mast	Clamps to mast up to 2" O.D.
Cable Type and Length	LMR-195, 12 inches
Connector.....	Type N jack

Since it is the intent of TELEX COMMUNICATIONS, INC. to continually improve its products, Telex reserves the right to make specification and design changes without notice.



8601 East Cornhusker Highway, Lincoln, NE 68505
Phone: (402) 467-5321 FAX: (402) 467-3279

<http://www.telexwireless.com>