

# Telex® Technical Data

5.8 GHz WLAN/UNII Directional Antenna

5.725 - 5.825 GHz

Order No. 5815AA

## General Description

This antenna is a totally enclosed 16 element Yagi antenna for the 5725 to 5825 MHz frequency band. It is designed to be used as a bridge antenna between two networks or for point to point communications. It has a nominal VSWR of 1.5:1 and is less than 2:1 over the entire frequency band. The gain is 14.0 dBi and the half-power beamwidth is 30 degrees. This antenna is normally mounted on a mast and is vertically polarized



## Specifications

### Electrical:

Frequency Range	5725-5825 MHz
VSWR	Less than 2:1, 1.5:1 Nominal
Nominal Impedance	50 ohms
Gain	14.0 dBi Nominal
Front-to-Back ratio	Greater than 20 dB
Half-power Beamwidth	30 degrees
Polarization	Vertical

### Mechanical:

Size	9.25" long
Mounting method	Clamps to vertical mast up to - 1 5/8" O.D.
Cable length	6"
Cable Type	RG-316/U Type, 50 ohm
Connector	SMA plug
Optional Connectors	RP-SMA or reverse-thread SMA

Since it is the intent of TELEX COMMUNICATIONS, INC. to continually improve its products, Telex reserves the right to make specification and design changes without notice.



8601 East Cornhusker Highway, Lincoln, NE 68505  
Phone: (402) 467-5321 FAX: (402) 467-3279