

Telex® Technical Data

WLAN/U-NII Omnidirectional Antenna

5.725 - 5.825 GHz

Order No. 5830AN

General Description

This antenna was designed for WLAN applications for frequencies of 5725 MHz to 5825 MHz. The antenna is omnidirectional and has a nominal gain of 7.5 dBi when measured at the standard Type N coax connector. This antenna is designed to be mounted on a round mast.



Specifications

Electrical:

Frequency Range.....	5725 - 5825 MHz
VSWR.....	nominal 1.4:1, maximum 2:1
Nominal Impedance	50 ohms
Nominal Gain.....	7.5 dBi
Half-power Elevation Beamwidth	15 degrees
Polarization	Vertical
Maximum Power	10 watts

Mechanical:

Size (without mount).....	1.0 OD x 10.875 inches
Mounting method	Bracket and SS clamp, 2.0 inch. OD mast max.
Connector	Type N jack
Wind Survival (per EIA-222-E at 100' height)	100 mph
Humidity	5% - 95% (non-condensing)

Since it is the intent of TELEX COMMUNICATIONS, INC. to continually improve its products, Telex reserves the right to make specification and design changes without notice.



8601 East Cornhusker Highway, Lincoln, NE 68505
Phone: (402) 467-5321 FAX: (402) 467-3279

<http://www.telexwireless.com>